

# Scott Bader CrusticROOF Topcoat Light Grey

Data Sheet

**NORTHEAST  
ROOFING LTD**

[www.neroofting.co.uk](http://www.neroofting.co.uk)



## SAFETY DATA SHEET

### CrysticROOF Topcoat Light Grey 6162

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME CrysticROOF Topcoat Light Grey 6162  
 PRODUCT NO. G10327  
 SUPPLIER Scott Bader  
 Wollaston  
 Wellingborough  
 Northamptonshire. NN29 7RL  
 +44(0)1933 663100  
 +44(0)1933 663693  
 reach@scottbader.com

#### 2 HAZARDS IDENTIFICATION

Flammable. Harmful by inhalation. Irritating to eyes and skin.

CLASSIFICATION Xn;R20. Xi;R36/38. R10.

##### ENVIRONMENT

The product is not expected to be hazardous to the environment.

##### PHYSICAL AND CHEMICAL HAZARDS

The product is flammable, and heating may generate vapours which may form explosive vapour/air mixtures.

##### HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Harmful by inhalation and in contact with skin. The product is irritating to eyes and skin.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
MALEIC ANHYDRIDE	203-571-6	108-31-6	<0.3%	C;R34 Xn;R22 R42/43
Solvent Naphtha (Petroleum), Light Aromatic (< 0,1% Benzene)	265-199-0	64742-95-6	<0.3%	Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.
STYRENE	202-851-5	100-42-5	25-30%	R10 Xn;R20 Xi;R36/38

The Full Text for all R-Phrases are Displayed in Section 16

##### COMPOSITION COMMENTS

Unsaturated polyester resin in reactive solvent.

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

##### INHALATION

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

##### INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

##### SKIN CONTACT

Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

##### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

## CrysticROOF Topcoat Light Grey 6162

### SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Keep combustibles away from spilled material. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Vapours are heavier than air and may spread near ground to sources of ignition.

### STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
STYRENE	WEL	100 ppm	430 mg/m3	250 ppm	1080 mg/m3	

WEL = Workplace Exposure Limit.

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. All handling to take place in well-ventilated area.

### RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Wear mask supplied with: Gas cartridge suitable for organic substances.

### HAND PROTECTION

Use protective gloves made of: Neoprene. Nitrile. Rubber (natural, latex).

### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

**CrysticROOF Topcoat Light Grey 6162****9 PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE	Viscous liquid
COLOUR	Grey
ODOUR	Solvent.
SOLUBILITY	Insoluble in water
BOILING POINT (°C)	50-150
RELATIVE DENSITY	1.10 - 1.20 25°C
FLASH POINT (°C)	32 CC (Closed cup).

**10 STABILITY AND REACTIVITY**

## STABILITY

Stable under normal temperature conditions.

## CONDITIONS TO AVOID

Avoid exposure to high temperatures or direct sunlight.

## HAZARDOUS POLYMERISATION

May polymerise.

## MATERIALS TO AVOID

Alkali metals. Strong oxidising substances. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

## HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

**11 TOXICOLOGICAL INFORMATION**

## GENERAL INFORMATION

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

## INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. Harmful by inhalation.

## INGESTION

Gastrointestinal symptoms, including upset stomach.

## SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema. Irritating to skin. Harmful in contact with skin.

## EYE CONTACT

Irritating and may cause redness and pain.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

The product is not expected to be hazardous to the environment.

**13 DISPOSAL CONSIDERATIONS**

## GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Make sure containers are empty before discarding (explosion risk). Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	3
PROPER SHIPPING NAME	RESIN SOLUTION
UN NO. ROAD	1866
UK ROAD PACK GR.	III

**CrysticROOF Topcoat Light Grey 6162**

ADR CLASS NO.	3
ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III
HAZARD No. (ADR)	30
ADR LABEL NO.	3
HAZCHEM CODE	3Y
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
RID CLASS NO.	3
RID PACK GROUP	III
UN NO. SEA	1866
IMDG CLASS	3
IMDG PAGE NO.	3
IMDG PACK GR.	III
EMS	F-E, S-E
MFAG	See Guide
MARINE POLLUTANT	No.
UN NO. AIR	1866
AIR CLASS	3
AIR PACK GR.	III

**15 REGULATORY INFORMATION**

## LABELLING



Harmful

## CONTAINS

STYRENE

## RISK PHRASES

R10	Flammable.
R20	Harmful by inhalation.
R36/38	Irritating to eyes and skin.

## SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.
S60	This material and its container must be disposed of as hazardous waste.
P14	Contains MALEIC ANHYDRIDE. May produce an allergic reaction.

## EU DIRECTIVES

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**16 OTHER INFORMATION**

REVISION DATE	15/05/2009
REV. NO./REPL. SDS GENERATED	1

**CrysticROOF Topcoat Light Grey 6162**

## RISK PHRASES IN FULL

R34	Causes burns.
R10	Flammable.
R20	Harmful by inhalation.
R22	Harmful if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R42/43	May cause sensitisation by inhalation and skin contact.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

## DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

## CONTACT:

### SOUTH SHIELDS:

12 Mackley Close  
South Shields  
NE34 0LJ

Tel: 0191 206 9710

### BISHOP AUCKLAND:

98 William Street  
Bishop Auckland  
DL14 8RJ

Tel: 01388 326 039

### EAST MIDLANDS:

Tel: 07565 581 889

Email: [info@neroofting.co.uk](mailto:info@neroofting.co.uk)

Website: [www.neroofting.co.uk](http://www.neroofting.co.uk)

**NORTHEAST  
ROOFING LTD**